



NO.	PART NAME	MATERIAL	Q'TY		REMARK
			SINGLE	DOUBLE	
1	FEEDBACK LEVER	STS304	1		
2	TERMINAL COVER	ALDC12	1		
3	BASE COVER	ALDC12	1		
4	PRESSURE GAUGE	STS304	1	2	
5	BASE BODY	ALDC12	1		
6	PILOT COVER	ALDC12	1		

- Earth (External, Internal)
- Minimum Size Wire 1mm or 18AWG.
 - M4*5 0.7P Round Head Screw
 - M4 Spring washer
- 2-Conduit Entry (G 1/2, 1/2 NPT, M20x1.5P)
- During connecting cable or conduits, it is necessary to follow flame-proof certified procedure or flame-proof certified cable gland or flexible coupling.

REV.NO.	REVISION DESCRIPTION	DRAWN / DATE	REVIEWED / DATE	APPROVED / DATE
△1	issue for approval	MDK/20090626	JCS/20090626	LYH/20090626
△1	Specifications update	MDK/20100305	JCS/20100305	LYH/20100305
△2	Dimension mark error correction	OSS/20120223	JCS/20120223	LYH/20120223
△3	Change Lever and Lever Spring	MDK/20121220	JCS/20121220	LYH/20121220
△4	Drawing arrangement	KBJ/20190903	KCH/20190903	KTJ/20190903

SPECIFICATIONS

Acting Type	<input type="checkbox"/> Single	<input type="checkbox"/> Double
Explosion Protection Type	<input type="checkbox"/> Non-Explosion	<input type="checkbox"/> Ex ia IIC T5/T6
Explosion Ambient Temp.	-40 ~ 80°C(T5) / -40 ~ 70°C(T6)	
Operating Temp.	-30 ~ 80°C (-22 ~ 176°F)	
Lever Type	<input type="checkbox"/> 10 ~ 40mm <input type="checkbox"/> 20 ~ 70mm <input type="checkbox"/> 50 ~ 100mm <input type="checkbox"/> 100 ~ 150mm	
Input Signal	4 ~ 20mA DC	
Supply Pressure	0.14 ~ 0.7 MPa(1.4 ~ 7 bar, 20 ~ 102 psi)	
Stroke	10 ~ 150mm (0.4" to 6")	
Impedance	Max 500 Ohm @ 20mA DC	
Conduit entry, Air Connection, Gauge Connection	<input type="checkbox"/> G 1/2, <input type="checkbox"/> Rc 1/4, <input type="checkbox"/> Rc 1/8 <input type="checkbox"/> G 1/2, <input type="checkbox"/> 1/4 NPT, <input type="checkbox"/> 1/8 NPT <input type="checkbox"/> G 1/2, <input type="checkbox"/> G 1/4, <input type="checkbox"/> 1/8 NPT <input type="checkbox"/> M20x1.5P, <input type="checkbox"/> 1/4 NPT, <input type="checkbox"/> 1/8 NPT	<input type="checkbox"/> 1/2 NPT, <input type="checkbox"/> 1/4 NPT, <input type="checkbox"/> 1/8 NPT
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Repeatability	±0.3% F.S.	
Main Board	MPU	16 bit Micro Controller
	A/D Converter	12 bit
	D/A Converter	12 bit
Communication	<input type="checkbox"/> None	<input type="checkbox"/> HART Communication
Option	<input type="checkbox"/> None	<input type="checkbox"/> Position Transmitter
Fail Option(Power)	<input type="checkbox"/> Fail Freeze	<input type="checkbox"/> Fail Safe
Air consumption	Fail Freeze	0.01 LPM (Sup. = 0.14 MPa)
	Fail Safe	6 LPM (Sup. = 0.14 MPa)
Flow Capacity	Fail Freeze	60 LPM (Sup. = 0.14 MPa)
	Fail Safe	40 LPM (Sup. = 0.14 MPa)
Output Characteristics	Linear, EQ%, Quick Open, User set	
Housing Material	Aluminum	
Ingress Protection	IP66	
Weight	3.0kg (6.61 lb)	

SURFACE TEXTURE	PRODUCT NAME	rotork Rotork YTC Limited GMP0-SI, KOREA
FINISH TREATMENT	SMART POSITIONER	
MATERIAL	MODEL	TITLE
OTHERWISE NOTE	PROJECTION	Linear
GENERAL TOLERANCE	SCALE	Positioner drawing
	3rd	1 / 3
	QUANTITY	DRAWING NO.
	1	YTC-2600L-01
		REV.
		4