



| REV.NO. | REVISION DESCRIPTION | DRAWN / DATE | REVIEWED / DATE | APPROVED / DATE |
|---------|-----------------------------|--------------|-----------------|-----------------|
| ① | First Issued | JCS/20110513 | | LYH/20110513 |
| | Ommision in the middle | | | |
| ② | Drawing arrangement | KSH/20161124 | JJS/20161124 | KTJ/20161124 |
| ③ | Drawing title block updated | KCH/20190801 | JJS/20190801 | KTJ/20190801 |

WARNING
 DO NOT connect Voltage source (9~28V DC) to Input (4~20mA DC) terminal (IN+, IN-) as it will cause PCB failure.

Wiring

IN+ — 4~20mA
 IN- — 4~20mA
 F.G —
 OUT+ — 9~28V DC
 OUT- — 9~28V DC

Button

UP DOWN ENTER ESC

Earth (External)

PROJECT NAME _____

| | | | | | |
|-------------------|--|------------------|--|---|--|
| SURFACE TEXTURE | | PRODUCT NAME | | Rotork YTC Limited <small>GMPO-SI, KOREA</small> | |
| FINISH TREATMENT | | SMART POSITIONER | | | |
| MATERIAL | | MODEL | | TITLE | |
| OTHERWISE NOTE | | YTC-3300, 3350 | | YT-3300/3350 + HART WIRING DIAGRAM | |
| GENERAL TOLERANCE | | PROJECTION | | DRAWING NO. | |
| | | 3rd | | 3300-05 | |
| | | QUANTITY | | REV. | |
| | | 1 | | 3 | |
| | | SHEET No. | | | |
| | | 1 / 1 | | | |